


100%
Recycled
Nylon

Equilibrium

Interface®



304200 Balance



304204 Entity



304205 Persistence



304282 Fluctuation



304207 Continuity



304216 Arrangement



304218 Coincidence



304213 Similarity



304201 Correlation




304293 Contentment



304296 Moderation



304295 Harmony



304262 Constant



304289 Serenity



304215 Integrity




304214 Classification



304202 Vitality




304286 Equation



304206 Analogy



304298 Uniformity



304208 Consistency



304211 Accuracy



304217 Ability




304212 Proportion



304203 Simplicity



304281 Mobility



304271 Parity



304287 Symmetry



304210 Unity



304209 Equality

Equilibrium



304282 Fluctuation, 304295 Harmony, 304298 Uniformity

Installed: Monolithic







Technical Specifications

Product Definition	Tufted Patterned Structured Tip Sheared Tile	
Konstruktion	Tuftgemusterte strukturierte Tip-Sheared - Schlingenqualität	
Descripción	Moqueta modular tufting bucle estructurado y pelo cortado con diseño	
Description	Dalle de moquette à velours tufté structuré, bouclé et rasé à motifs	
Type	Getufte gestructureerde tip sheared bouclé	
Descrizione	Bouclé tufted strutturato rasato	
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre- and post-consumer recycled content	
Polfasermaterial	100% recyceltes Polyamid garmgefärbt mit recyceltem Anteil (Prä- und Post- Konsumenten-Anteil)	
Composición Fibra	100% Poliamida reciclada BCF tintada en masa con contenido reciclado pre y post-consumo	
Composition	Fibre polyamide BCF 100% recyclée teint en masse contenant des éléments recyclés pré et post-consommation	
Poolmaterialaal	100% gerecycled Solution Dyed Polyamide BCF, bevat pre- en post-consumer gerecycled content	
Fibra	100% Poliammide BCF tinta in massa con contenuto riciclato pre- e post- consumer	
Pile Yarn Weight / Poleinsatzgewicht / Peso Fibra	814g/m² ± 5%	
/ Poids de fibre / Poolinzetgewicht / Peso Felpa		
Total Weight / Gesamtgewicht / Peso Total	4810g/m² ± 5%	
Poids total / Totaalgewicht / Peso Totale		
Pile Height / Polschichtdicke / Altura Fibra /	4.5 mm ± 0.3 mm	
Hauteur de la fibre / Poolhoogte / Altezza Felpa		
Total Thickness / Gesamtdicke / Espesor Total / Epaisseur totale / Totale dikte / Altezza Totale	7.7 mm ± 0.5 mm	
Gauge/Ends 10 cm / Teilung x 10 cm / Galga x 10 cm / Jauge-Rangs par 10 cm / Rijen per 10 cm / Serraggio x 10 cm	1/12 – 47.2	
Tufts per m² / Noppenzahl/m² / Puntadas m² / Densité du tuft par m² / Aantal noppen per m² / Densità Punti	167,560 ± 5%	
Backing Type / Rückenkonstruktion / Soporte / Sous-couche / Ruguitvoering / Sottofondo	Graphlex®	
Wear Classification / Beanspruchungsklasse / Clasificación al tráfico / Classement Gebruiksintensiteit / Resistenza all'usura	Heavy Contract (EN 1307) Class 33 / LC2	

Style	33802
4m² - 16 tiles per box (50 x 50 cm ± 0.15%)	

Radiant Panel / Schwerentflammbarkeit	(EN ISO 9239/1)Euroclass Bfl s1 (EN ISO 13501)
Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Dimensional Stability / Dimensionsstabilität	≤ 0.2% (ISO 2551 / EN 986)
Estabilidad Dimensional / Stabilité dimensionnelle	
Dimensionele stabiliteit / Test Stabilità dimensionale	

Sound Absorption					
125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
0.02	0.03	0.12	0.27	0.35	0.45

EN 14041

DOP: 1037/113790

textile floor covering

EN 1307

Monolithic

Quarter Turn

Ashlar

Cert. ENP 477

28dB

≥ 2.4

6

0.20

Bfl-s1

DS

<10³J

Interface European Manufacturing BV reserve the right to change or modify specifications.

Die Interface European Manufacturing BV behält sich das Recht vor, Produktspezifikationen zu ändern oder entsprechend anzupassen.

Interface European Manufacturing BV se reserva el derecho a modificar las especificaciones arriba referenciadas.

Interface European Manufacturing BV se réserve la possibilité de modifier les caractéristiques ci-dessus.

Interface European Manufacturing BV behoudt zich het recht voor de specificaties te allen tijde aan te passen.

Interface European Manufacturing BV si riserva il diritto di modificare le proprie specifiche tecniche senza preavviso.

For full environment data, visit:
www.interface.com/eds

Visit our design blog at:
www.designwithpurposeblog.com

Light Value

Product	Colour No	Colour Name	L Value*	Y Value*
Equilibrium	304200	Balance	66.7	36.2
	304201	Correlation	53.0	21.1
	304202	Vitality	48.8	17.4
	304203	Simplicity	65.1	34.1
	304204	Entity	55.7	23.6
	304205	Persistence	38.3	10.2
	304206	Analogy	24.9	4.4
	304207	Continuity	24.8	4.3
	304208	Consistency	20.0	3.0
	304209	Equality	25.6	4.6
	304210	Unity	20.1	3.0
	304211	Accuracy	27.1	5.1
	304212	Proportion	20.7	3.2
	304213	Similarity	43.3	13.3
	304214	Classification	32.1	7.1
	304215	Integrity	44.1	13.9
	304216	Arrangement	29.5	6.1
	304217	Ability	25.4	4.6
	304218	Coincidence	30.1	6.3
	304262	Constant	19.0	2.7
	304271	Parity	16.7	2.2
	304281	Mobility	46.7	15.8
	304282	Fluctuation	52.2	20.3
	304286	Equation	56.2	24.1
	304287	Symmetry	40.7	11.7
	304289	Serenity	33.8	7.9
	304293	Contentment	44.0	13.8
	304295	Harmony	42.3	12.7
	304296	Moderation	31.8	7.0
	304298	Uniformity	30.7	6.5

* **Light Value:** L Value = L according to CIE L*a*b* colour space, Y Value = Light Reflectance Value according to BS 8493

Lichtreflexionswerte: L-Wert = L gemäß CIE L*a*b* Farbspektrum, Y-Wert = Lichtreflexionswert gemäß British Standard BS 8493

Valores de Reflectancia de Luz: Valor L= L según CIE L*a*b* espacio de color, Valor Y = Valor de reflectancia de luz según el estándar británico BS 8493

Valeurs concernant la lumière: Valeur L = L faisant référence à la méthode CIE L*a*b* pour la couleur , Valeur Y = Valeurs de réflectance de la lumière selon le British Standard BS 8493

Licht waarden: L Waarde = L volgens CIE L*a*b*kleurruimte, Y Waarde = Licht Reflectie Waarde volgens BS 8493

Indici di riflettanza alla luce: Indice L= L secondo CIE L*a*b* colour space, IndiceY= Indice di riflettanza alla luce secondo la norma BS 8493

Environmental Data Sheet

Construction			
Yarn system	100% BCF Solution Dyed PA 6		
Backing system	Graphlex®		
Recycled Content	Total Recycled Content	Pre consumer	Post consumer
Product average	62,38%	53,96%	8,42%
Yarn average	100,00%	50,00%	50,00%
Recycled content can be subject to differences between colours. See details for individual colours on next page.			
Carbon Footprint			
Full life-cycle carbon footprint (following our EPD results or EPD calculation method)	Global Warming Potential (kgs CO2 equivalents/sq meter)		
	Raw materials and Production:		8.47 kg CO ₂ eq./m ²
	Delivery and installation:		0.53 kg CO ₂ eq./m ²
	Use (10 years):		2.92 kg CO ₂ eq./m ²
	End of life (waste to energy):		8.76 kg CO ₂ eq./m ²
TOTAL (10 years' lifetime):		20.68 kg CO ₂ eq./m ²	
CO ₂ compensation	Carbon neutral Cool Carpet® is standard		
Manufacturing			
Location	Scherpenzeel, NL		
	Factory is certified ISO 14001 since 1996 and ISO 9001 since 1990		
Installation Impacts			
TacTiles™	Optimised for glue-free installation with TacTiles™ connectors with virtually zero VOCs		
Installation Waste	In a typical installation* using the installation method below:		
	Quarter turn – 3-4% installation waste		
	Ashlar – 3-5% installation waste		
	Monolithic - 3-4% installation waste		
	For reference: 2 metre wide broadloom typically generates 7-10 % installation waste		
	* In a rectangular building, installed before walls.		
End-of-life			
Alternatives to landfill	Reuse: Can be cleaned and reused in a non-critical location to extend its useful life		
	Recycling: Can be returned through the Interface ReEntry scheme and be re-used as raw material in new carpet tiles		
	Waste-to-Energy: Can be incinerated in appropriate waste to energy plant		
Indoor Air Quality			
GUT (Gemeinschaft umweltfreundlicher Teppichboden)	The product passes all requirements of GUT's testing criteria regarding hazardous substances, emissions and odour.		
	GUT PRODIS Certificate no. 84479CB4		
CRI (Carpet & Rug Institute)	Compliant to the requirements of the Green Label Plus programme.		
Compliance to Green Building Schemes			
See next page to check how our products contribute to the main green building certification schemes (BREEAM, LEED, HQE and DGNB)			
Type III Environmental Product Declaration			
EPD according to ISO 14025	This product is covered by the Environmental Product Declaration EPD-IFF-20120021-CBD1-EN		

Recycled content – colour level						
Colourway	Total recycled content	Pre consumer recycled content	Post consumer recycled content	Yarn recycled content	Pre consumer recycled content	Yarn post consumer recycled content
304281 Mobility	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304293 Contentment	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304298 Uniformity	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304287 Symmetry	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304296 Moderation	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304286 Equation	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304271 Parity	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304289 Serenity	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304282 Fluctuation	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304295 Harmony	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304262 Constant	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304200 Balance	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304201 Correlation	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304202 Vitality	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304203 Simplicity	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304204 Entity	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304205 Persistence	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304206 Analogy	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304207 Continuity	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304208 Consistency	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304209 Equality	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304210 Unity	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304211 Accuracy	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304212 Proportion	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304213 Similarity	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304214 Classification	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304215 Intergrity	61,9%	53,5%	8,4%	100,00%	50,00%	50,00%
304216 Arrangement	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304217 Ability	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%
304218 Coincidence	62,8%	54,4%	8,4%	100,00%	50,00%	50,00%

Compliance to Green Building Schemes	
BREEAM (UK and international)	BRE Green Guide Ratings: Office - A rated Education - A+ rated Health Care - A+ rated Retail (by fashion) - A+ rated Potential contribution to following categories and credits: Hea 02 - Indoor air quality – minimising sources of air pollution Hea 05 - Acoustic Performance Mat 01 - Life Cycle Impacts Mat 05 - Designing for robustness Wst 01 - Construction Waste Management
LEED 2009 US	Potential direct or indirect contribution to following categories and credits: Indoor Environmental Quality Credit 4.1 Low Emitting Materials: Adhesive & Sealants Credit 4.3 Low Emitting Materials: Carpet Systems Materials and Resources Credit 2.1 Construction Waste Management Credit 4.1 Recycled content Credit 5.1 Regional Materials Innovation and Design Credits 1-4 1 Pilot Credit 43, Certified Products
HQE (FR)	Potential direct or indirect contribution to several points within following targets: 2. Integrated choice of products and construction materials 3. Low site nuisance 9. Acoustic comfort 10. Visual comfort 11. No unpleasant smells 12. Sanitary quality of areas 13. Sanitary air quality
DGNB (D)	Potential direct or indirect contribution to following criterion ENVIRONMENTAL QUALITY ENV1.2 Local Environmental Impact ECONOMIC QUALITY ECO1.1 Building-Related Lifecycle Costs ECO2.1 Efficient Use of Space SOCIOCULTURAL AND FUNCTIONAL QUALITY SOC1.2 Indoor Air Quality SOC1.3 Acoustic Comfort TECHNICAL QUALITY TEC1.5 Ease of Cleaning and Maintenance TEC1.6 Ease of Dismantling and Recycling

Services



TacTiles™

- A smarter, more sustainable way to install carpet tiles
- No need for liquid adhesives
- Fitting tiles is quick, clean and easy and the process virtually eliminates emissions
- No damage to sub floors, and nothing to stop you lifting or moving the carpet whenever you want



Entrance Matting

Incredibly tough, hard-wearing and practical; indoor entrance matting acts as the first line of defence to any interior by removing almost 100% of dirt, rain and mud before it's walked into your flooring.

Both of the products in our commercial entrance matting range – Barricade and Foyer – are resilient, functional, easy to maintain and stylish. And it's for these reasons that our barrier matting forms an essential part of any maintenance programme needed to keep your floorcovering looking its very best.