



Infuse & Composure

Interface®



Composure - 303001 Reflect
Installed: Non Directional
Infuse - 333451 Ash/Almond
Installed: Brick

Infuse & Composure



Infuse - 333461 Jubilee/Jade



Composure - 303006 Calm




Infuse - 333460 Jubilee/Plum



Heuga 530
5073 Ivy



Heuga 727
672741 Aegean Sea (PD)



Heuga 530
5070 Blue Moon



Heuga 727
672726 Fuchsia (PD)



Infuse - 333451 Ash/Almond



Composure - 303001 Reflect



Infuse - 333450 Ash/Lupin



Heuga 530
5055 Silver



Heuga 727
672713 Oyster (SD)



Heuga 530
5074 Midnight



Heuga 727
672734 Lavender (SD)

Infuse & Composure



Infuse - 333454 Graphite/Ruby



Composure - 303003 Solitude



Infuse - 333455 Graphite/Pine



Infuse - 333456 Barley/Honey




Composure - 303004 Tranquil




Infuse - 333457 Barley/Truffle




Heuga 530
5062 Volcano



Heuga 727
672722 Opera (SD)



Heuga 530
5058 Black



Heuga 727
672748 Jungle (PD)




Heuga 530
5059 Sand



Heuga 727
672714 Linen (SD)



Heuga 530
5057 Basalt



Heuga 727
672710 Copra (SD)



Infuse - 333452 Clay/Lime



Composure - 303002 Diffuse



Infuse - 333453 Clay/Cobalt



Infuse - 333458 Mink/Duck Egg




Composure - 303005 Serene



Infuse - 333459 Mink/Herb



Heuga 530
5071 Lime



Heuga 727
672746 Pistachio (PD)




Heuga 530
5069 Lobelia




Heuga 727
672737 Lagoon (PD)




Heuga 530
5067 Santorin



Heuga 727
672705 Dust (SD)



Heuga 530
5063 Ginger



Heuga 727
672710 Copra (SD)



Composure - 303002 Diffuse
Infuse - 333452 Clay/Lime
Heuga 530 - 5071 Lime

Installed: Non Directional
Installed: Ashlar
Installed: Monolithic



Composure - 303005 Serene
Infuse - 333458 Mink/Duck Egg
Heuga 530 - 5067 Santorin

Installed: Non Directional
Installed: Ashlar
Installed: Monolithic

Technical Specifications

Infuse

Product Definition	Tufted Patterned Structured Loop Tile
Konstruktion	Tuftgemusterte strukturierte Schlingenqualität
Descripción	Moqueta modular tufting bucle estructurado con diseño
Description	Dalle de moquette à velours tufté bouclé structuré à motifs
Type	Getufte gedessineerde gestructureerde bouclé
Descrizione	Bouclè tufted strutturato

Pile Material	100% BCF Solution Dyed Nylon
	contains pre-consumer recycled content
Polfasermaterial	100% Polyamid garngefärbt mit recyceltem Anteil (Prä-Konsumenten-Anteil)
Composición Fibra	100% Poliamida BCF tintada en masa con contenido reciclado pre-consumo
Composition	100% Poyamide BCF Teint en masse contenant des éléments recyclés pré-consommation
Poolateriaaal	100% Solution Dyed Polyamide BCF, bevat pre-consumer gerecycled content
Fibra	100% Poliammide BCF tinta in massa con contenuto riciclato pre-consumer

Pile Yarn Weight / Poleinsatzgewicht / Peso Fibra	587g/m² ± 10%
/ Poids de fibre / Poolinzetgewicht / Peso Felpa	
Effective Pile Yarn Weight / Polschichtgewicht	425g/m² ± 10%
/ Peso útil de fibra / Poids de fibre utile Effectief poolgewicht / Peso felpa effettivo	
Total Weight / Gesamtgewicht / Peso Total	4482g/m² ±5%
Poids total / Totaalgewicht / Peso Totale	
Pile Height / Polschichtdicke / Altura Fibra /	3.4 mm ± 0.5 mm
Hauteur de la fibre / Poolhoogte / Altezza Felpa	
Total Thickness / Gesamtdicke / Espesor Total /	6.8 mm ± 0.5 mm
Epaisseur totale / Totale dikte / Altezza Totale	
Gauge/Ends 10 cm / Teilung x 10 cm /	1/10 – 39.4
Galga x 10 cm / Jauge-Rangs par 10 cm	
/ Rijen per 10 cm / Serraggio x 10 cm	
Tufts per m² / Noppenzahl/m² / Puntadas m² /	173,360 ±7.5%
Densité du tuft par m² / Aantal noppen per m² /	
Densità Punti	
Backing Type / Rückenkonstruktion / Soorte /	Graphlex®
Sous-couche / Ruguitvoering / Sottofondo	
Wear Classification / Beanspruchungsklasse	Heavy Contract
/ Clasificación al tráfico / Classement	
(EN 1307) Class 33/LC2	
Gebruiksintensiteit / Resistenza all'usura	

Style	33345
4m² - 16 tiles per box (50 x 50 cm ± 0.2%)	
(EN ISO 9239/1) Euroclass	
Radiant Panel /	Cfl s1 (EN ISO 13501)
Schwerentflammbarkeit	
Pass, low radius of effects	
Hot Metal Nut	of ignition (BS 4790)
≤ 0.2%	
Dimensional Stability / Dimensionsstabilität	(ISO 2551 / EN 986)

Estabilidad Dimensional / Stabilité dimensionnelle
Dimensionele stabiliteit / Test Stabilità dimensionale

Sound Absorption
125Hz 250Hz 500Hz 1000Hz 2000Hz 4000Hz
0.02 0.04 0.07 0.22 0.31 0.37

EN 14041

CE

DOP: 1037/120947

textile floor covering

EN 1307

↑↑↑↑

Ashlar

↑↑↑↑

Brick

↑↑

↑↑

↑↑

↑↑

26dB

≥ 2.4

≥7

0.15

Environmental Data Sheet - Infuse



Construction			
Yarn system	BCF Solution Dyed Nylon (PA6.6)		
Backing system	Graphlex®		
Recycled Content	Total	Pre Consumer	Post Consumer
Yarn average	20,38%	20,38%	0,00%
Product average	50,90%	50,90%	0,00%
Recycled content can be subject to differences between colours. See details for individual colours on next page.			
Carbon Footprint	Global Warming Potential (kgs CO2 equivalents/sq meter)		
Full life-cycle carbon footprint (following our EPD results or EPD calculation method)	Raw materials and Production:	8.3 kg CO ₂ eq./m²	
	Delivery and installation:	0.32 kg CO ₂ eq./m²	
	Use (10 years):	2 kg CO ₂ eq./m²	
	End of life (waste to energy):	4.6 kg CO ₂ eq./m²	
	TOTAL (10 years¹ lifetime):	15.22 kg CO ₂ eq./m²	
CO ₂ compensation	Carbon neutral Cool Carpet® is optional		
Manufacturing			
Location	Scherpenzeel, NL		
	Factory is certified ISO 14001 since 1996 and ISO 9001 since 1990		
Installation Impacts			
TacTiles™	Optimised for glue-free installation with TacTiles™ connectors with virtually zero VOCs		
Installation Waste	In a typical installation* using the installation method below:		
	Ashlar - 3-5% installation waste		
	Brick - 3-5% installation waste		
	For reference: 2 metre wide broadloom typically generates 7-10 % installation waste		
	* In a rectangular building, installed before walls.		
End-of-life			
Alternatives to landfill	Reuse: Can be cleaned and reused in a non-critical location to extend its useful life		
	Recycling: Can be returned through the Interface ReEntry scheme and be re-used as raw material in new carpet tiles		
	Waste-to-Energy: Can be incinerated in appropriate waste to energy plant		
Indoor Air Quality			
GUT (Gemeinschaft umweltfreundlicher Teppichboden)	The product passes all requirements of GUT's testing criteria regarding hazardous substances, emissions and odour.		
	GUT PRODIS certificate : Applied for		
CRI (Carpet & Rug Institute)	Compliant to LEED IQ 4.3 credit (tested in Eurofins to the equivalent test of the CRI Green Label Plus)		
Compliance to Green Building Schemes			
	See next page to check how our products contribute to the main green building certification schemes (BREEAM, LEED, HQE and DGNB)		
Type III Environmental Product Declaration			
EPD according to ISO 14025	This product is covered by the Environmental Product Declaration EPD-IFF-2011711-E		

Recycled content – colour level						
Colourway	Total Recycled Content	Pre consumer recycled content	Post consumer recycled content	Total yarn recycled content	Yarn pre-consumer	Yarn post-consumer
333450 Ash/Lupin	50,2%	50,2%	0,0%	18,01%	18,01%	0,00%
333451 Ash/Almond	50,1%	50,1%	0,0%	17,82%	17,82%	0,00%
333452 Clay/Lime	51,1%	51,1%	0,0%	18,99%	18,99%	0,00%
333453 Clay/Cobalt	51,2%	51,2%	0,0%	19,27%	19,27%	0,00%
333454 Graphite/Ruby	51,6%	51,6%	0,0%	22,58%	22,58%	0,00%
333455 Graphite/Pine	51,6%	51,6%	0,0%	22,66%	22,66%	0,00%
333456 Barley/Honey	50,5%	50,5%	0,0%	20,37%	20,37%	0,00%
333457 Barley/Truffle	50,5%	50,5%	0,0%	20,18%	20,18%	0,00%
333458 Mink/Duck Egg	50,5%	50,5%	0,0%	20,55%	20,55%	0,00%
333459 Mink/Herb	50,4%	50,4%	0,0%	19,54%	19,54%	0,00%
333460 Jubilee/Plum	51,5%	51,5%	0,0%	21,50%	21,50%	0,00%
333461 Jubilee/Jade	51,7%	51,7%	0,0%	23,04%	23,04%	0,00%

Compliance to Green Building Schemes	
BREEAM (UK and international)	BRE Green Guide Ratings: Office - Not Available Education - Not Available Health Care - Not Available Retail (by fashion) - Not Available Potential contribution to following categories and credits: Hea 02 - Indoor air quality – minimising sources of air pollution Hea 05 - Acoustic Performance Mat 01 - Life Cycle Impacts Mat 05 - Designing for robustness Wst 01 - Construction Waste Management
LEED 2009 US	Potential direct or indirect contribution to following categories and credits: Indoor Environmental Quality Credit 4.1 Low Emitting Materials: Adhesive & Sealants Credit 4.3 Low Emitting Materials: Carpet Systems Materials and Resources Credit 2.1 Construction Waste Management Credit 4.1 Recycled content Credit 5.1 Regional Materials Innovation and Design Credits 1-4 1 Pilot Credit 43, Certified Products
HQE (FR)	Potential direct or indirect contribution to several points within following targets: 2. Integrated choice of products and construction materials 3. Low site nuisance 9. Acoustic comfort 10. Visual comfort 11. No unpleasant smells 12. Sanitary quality of areas 13. Sanitary air quality
DGNB (D)	Potential direct or indirect contribution to following criterion ENVIRONMENTAL QUALITY ENV1.2 Local Environmental Impact ECONOMIC QUALITY ECO1.1 Building-Related Lifecycle Costs ECO2.1 Efficient Use of Space SOCIOCULTURAL AND FUNCTIONAL QUALITY SOC1.2 Indoor Air Quality SOC1.3 Acoustic Comfort TECHNICAL QUALITY TEC1.5 Ease of Cleaning and Maintenance TEC1.6 Ease of Dismantling and Recycling

Environmental Data Sheet - Composure



Construction			
Yarn system	BCF Solution Dyed Nylon (PA6.6)		
Backing system	Graphlex®		
Recycled Content	Total	Pre Consumer	Post Consumer
Yarn average	20,52%	19,69%	0,83%
Product average	51,82%	51,72%	0,10%
Recycled content can be subject to differences between colours. See details for individual colours on next page.			
Carbon Footprint	Global Warming Potential (kgs CO2 equivalents/sq meter)		
Full life-cycle carbon footprint (following our EPD results or EPD calculation method)	Raw materials and Production:		8.3 kg CO ₂ eq./m ²
	Delivery and installation:		0.32 kg CO ₂ eq./m ²
	Use (10 years):		2 kg CO ₂ eq./m ²
	End of life (waste to energy):		4.6 kg CO ₂ eq./m ²
	TOTAL (10 years' lifetime):		15.22 kg CO ₂ eq./m ²
CO ₂ compensation	Carbon neutral Cool Carpet® is standard		
Manufacturing			
Location	Scherpenzeel, NL		
	Factory is certified ISO 14001 since 1996 and ISO 9001 since 1990		
Installation Impacts			
TacTiles™	Optimised for glue-free installation with TacTiles™ connectors with virtually zero VOCs		
Installation Waste	In a typical installation* using the installation method below:		
	Non directional - 1 to 2% installation waste		
	For reference: 2 metre wide broadloom typically generates 7-10 % installation waste		
	* In a rectangular building, installed before walls.		
End-of-life			
Alternatives to landfill	Reuse: Can be cleaned and reused in a non-critical location to extend its useful life		
	Recycling: Can be returned through the Interface ReEntry scheme and be re-used as raw material in new carpet tiles		
	Waste-to-Energy: Can be incinerated in appropriate waste to energy plant		
Indoor Air Quality			
GUT (Gemeinschaft umweltfreundlicher Teppichboden)	The product passes all requirements of GUT's testing criteria regarding hazardous substances, emissions and odour.		
	GUT PRODIS certificate : Applied for		
CRI (Carpet & Rug Institute)	Compliant to LEED IQ 4.3 credit (tested in Eurofins to the equivalent test of the CRI Green Label Plus)		
Compliance to Green Building Schemes			
	See next page to check how our products contribute to the main green building certification schemes (BREEAM, LEED, HQE and DGNB)		
Type III Environmental Product Declaration			
EPD according to ISO 14025	This product is covered by the Environmental Product Declaration EPD-IFF-2011711-E		

Recycled content – colour level						
Colourway	Total Recycled Content	Pre consumer recycled content	Post consumer recycled content	Total yarn recycled content	Yarn pre-consumer	Yarn post-consumer
303001 Reflect	51,20%	51,20%	0,00%	18,89%	18,89%	0,00%
303002 Diffuse	51,50%	51,50%	0,00%	21,06%	21,06%	0,00%
303003 Solitude	51,70%	51,70%	0,00%	23,05%	23,05%	0,00%
303004 Tranquil	51,40%	51,40%	0,00%	20,39%	20,39%	0,00%
303005 Serene	51,40%	51,40%	0,00%	20,73%	20,73%	0,00%
303006 Calm	51,80%	51,80%	0,00%	23,56%	23,56%	0,00%

Compliance to Green Building Schemes	
BREEAM (UK and international)	BRE Green Guide Ratings: Office - Not Available Education - Not Available Health Care - Not Available Retail (by fashion) - Not Available Potential contribution to following categories and credits: Hea 02 - Indoor air quality – minimising sources of air pollution Hea 05 - Acoustic Performance Mat 01 - Life Cycle Impacts Mat 05 - Designing for robustness Wst 01 - Construction Waste Management
LEED 2009 US	Potential direct or indirect contribution to following categories and credits: Indoor Environmental Quality Credit 4.1 Low Emitting Materials: Adhesive & Sealants Credit 4.3 Low Emitting Materials: Carpet Systems Materials and Resources Credit 2.1 Construction Waste Management Credit 4.1 Recycled content Credit 5.1 Regional Materials Innovation and Design Credits 1-4 1 Pilot Credit 43, Certified Products
HQE (FR)	Potential direct or indirect contribution to several points within following targets: 2. Integrated choice of products and construction materials 3. Low site nuisance 9. Acoustic comfort 10. Visual comfort 11. No unpleasant smells 12. Sanitary quality of areas 13. Sanitary air quality
DGNB (D)	Potential direct or indirect contribution to following criterion ENVIRONMENTAL QUALITY ENV1.2 Local Environmental Impact ECONOMIC QUALITY ECO1.1 Building-Related Lifecycle Costs ECO2.1 Efficient Use of Space SOCIOCULTURAL AND FUNCTIONAL QUALITY SOC1.2 Indoor Air Quality SOC1.3 Acoustic Comfort TECHNICAL QUALITY TEC1.5 Ease of Cleaning and Maintenance TEC1.6 Ease of Dismantling and Recycling



TacTiles™

- A smarter, more sustainable way to install carpet tiles
- No need for liquid adhesives
- Fitting tiles is quick, clean and easy and the process virtually eliminates emissions
- No damage to sub floors, and nothing to stop you lifting or moving the carpet whenever you want



Entrance Matting

Incredibly tough, hard-wearing and practical; indoor entrance matting acts as the first line of defence to any interior by removing almost 100% of dirt, rain and mud before it's walked into your flooring.

Both of the products in our commercial entrance matting range – Barricade and Foyer – are resilient, functional, easy to maintain and stylish. And it's for these reasons that our barrier matting forms an essential part of any maintenance programme needed to keep your floorcovering looking its very best.